

IN THE CLAIMS

Please **CANCEL** claims 1-90, without prejudice or disclaimer,  
and before calculating the filing fees for the present application.

Please **ADD** the following NEW claims:

91. (NEW) A repeater comprising:  
a first amplifier amplifying an optical signal;  
a first dispersion compensator providing dispersion compensation to the amplified optical signal; and  
a second amplifier amplifying the optical signal provided with dispersion compensation by the first dispersion compensator.

92. (NEW) A repeater as in claim 91, further comprising:  
a second dispersion compensator providing dispersion compensation to the optical signal after being amplified by the first amplifier and before being amplified by the second amplifier.

93. (NEW) A repeater as in claim 92, wherein the first and second dispersion compensators provide different dispersion compensation amounts.

94. (NEW) A repeater as in claim 92, wherein  
the first dispersion compensator provides positive dispersion  
compensation, and  
the second dispersion compensator provides negative dispersion

*at  
cont.*  
compensation.

95. (NEW) A repeater as in claim 91, wherein the first and second amplifiers are erbium doped optical fiber amplifiers.

96. (NEW) A repeater as in claim 92, wherein the first and second amplifiers are erbium doped fiber amplifiers.

97. (NEW) A repeater as in claim 91, wherein the first dispersion compensator is a dispersion compensation fiber.

98. (NEW) A repeater as in claim 92, wherein the first and second dispersion compensators are dispersion compensation fibers.

99. (NEW) A repeater as in claim 91, wherein the first and second amplifiers have a combined gain so that the optical signal is output from the second amplifier at a power level sufficient to be received by a receiver downstream of the second amplifier.

100. (NEW) A repeater as in claim 92, wherein the first and second amplifiers have a combined gain so that the optical signal is output from the second amplifier at a power level sufficient to be received by a receiver downstream of the second amplifier.

866750-60603060

a dispersion compensator providing dispersion

at  
ent.  
compensation to the optical signal either before or after being amplified by the optical amplifier.

106. (NEW) A repeater as in claim 105, wherein the optical amplifier of each dispersion compensator unit is an erbium doped fiber amplifier.

107. (NEW) A repeater as in claim 105, wherein the dispersion compensator of each dispersion compensator unit is a dispersion compensation fiber.

108. (NEW) A repeater comprising:  
an optical amplifier amplifying an optical signal; and  
first and second dispersion compensators providing dispersion compensation to the optical signal.

109. (NEW) A repeater as in claim 108, wherein the first and second dispersion compensators both provide dispersion compensation to the optical signal before being amplified by the optical amplifier.

110. (NEW) A repeater as in claim 108, wherein the first and second dispersion compensators both provide dispersion compensation to the optical signal after being amplified by the optical

2008-09-05 10:00:00

amplifier.

111. (NEW) A repeater as in claim 108, wherein at least one of the group consisting of the first and second dispersion compensators provides dispersion compensation to the optical signal before being amplified by the optical amplifier.

112. (NEW) A repeater as in claim 108, wherein at least one of the group consisting of the first and second dispersion compensators provides dispersion compensation to the optical signal after being amplified by the optical amplifier.

113. (NEW) A repeater as in claim 108, wherein the first and second dispersion compensators provide different dispersion compensation amounts to the optical signal.

114. (NEW) A repeater as in claim 111, wherein the first and second dispersion compensators provide different dispersion compensation amounts to the optical signal.

115. (NEW) A repeater as in claim 112, wherein the first and second dispersion compensators provide different dispersion compensation amounts to the optical signal.

119. (NEW) An apparatus as in claim 118, wherein the first and second dispersion compensators provide different dispersion compensation amounts.

120. (NEW) An apparatus as in claim 118, wherein  
the first dispersion compensator provides positive dispersion  
compensation, and  
the second dispersion compensator provides negative dispersion  
compensation.

121. (NEW) An apparatus as in claim 117, wherein the first and second amplifiers are erbium doped fiber amplifiers.

122. (NEW) An apparatus as in claim 118, wherein the first and second amplifiers are erbium doped fiber amplifiers.

123. (NEW) ~~An apparatus as in claim 117, wherein the first dispersion compensator is a dispersion compensation fiber.~~

124. (NEW) An apparatus as in claim 118, wherein the first and second dispersion compensators are dispersion compensation fibers.

125. (NEW) An apparatus as in claim 117, wherein the first and second amplifiers have a combined gain so that the optical signal is output from the second amplifier at a power level sufficient to be received by a receiver downstream of the second amplifier.

An apparatus as in  
fiers have a combin  
t from the second  
received by a recei

An apparatus as in c  
dispersion compens  
the optical signal  
nd before being ampl  
sion compensator bei

An apparatus as in  
rd dispersion comp  
nsation amounts.

An apparatus compri  
y of dispersion c  
ies, each dispersion  
ical amplifier for a  
spersion compensa  
the optical signal  
optical amplifier,  
closure housing the

rd disp  
nsation

rd disp  
nsation

rd disp  
nsation  
An appa  
y of d  
ies, eac  
ical amp  
spersion  
the opt.  
optical  
closure



dispersion compensator.

130. (NEW) An apparatus as in claim 129, wherein the optical amplifier of each dispersion compensator unit is an erbium doped fiber amplifier.

131. (NEW) An apparatus as in claim 129, wherein the dispersion compensator of each dispersion compensator unit is a dispersion compensation fiber.

132. (NEW) An apparatus comprising:  
an optical amplifier amplifying an optical signal;  
first and second dispersion compensators providing dispersion compensation to the optical signal; and  
an enclosure housing the optical amplifier and the first and second dispersion compensators.

133. (NEW) An apparatus as in claim 132, wherein the first and second dispersion compensators both provide dispersion compensation to the optical signal before being amplified by the optical amplifier.

134. (NEW) An apparatus as in claim 132, wherein the first and second dispersion compensators both provide dispersion compensation to the optical signal after being amplified by the optical amplifier.

135. (NEW) An apparatus as in claim 132, wherein at least one of the group consisting of the first and second dispersion compensators provides dispersion compensation to the optical signal before being amplified by the optical amplifier.

136. (NEW) An apparatus as in claim 132, wherein at least one of the group consisting of the first and second dispersion compensators provides dispersion compensation to the optical signal after being amplified by the optical amplifier.

137. (NEW) An apparatus as in claim 132, wherein the first and second dispersion compensators provide different dispersion compensation amounts to the optical signal.

138. (NEW) An apparatus as in claim 135, wherein the first and second dispersion compensators provide different dispersion compensation amounts to the optical signal.

000000-051998

**THE UNIVERSITY OF CHICAGO**

ing of the  
es dispersio  
ied by the

ing of the  
es dispersio  
ied by the

apparatus  
compensator p

apparatus  
compensator p

apparatus  
compensator p

Attorney Docket No. 1075.1013-CC-D3

~~at~~  
~~and.~~

144. (NEW) An apparatus as in claim 142, wherein the first and second amplifiers are erbium doped fiber amplifiers.

146. (NEW) An apparatus as in claim 142, further comprising:  
an enclosure which houses the dispersion compensator and the  
second amplifier.

148. (NEW) A repeater as in claim 147, wherein the first and second amplifiers are erbium doped optical fiber amplifiers.

at  
cont. 149. (NEW) A repeater as in claim 147, wherein the first dispersion compensator is a dispersion compensation fiber.

150. (NEW) A repeater as in claim 147, wherein the first and second amplifiers have a combined gain so that the plurality of optical signals are output from the second amplifier at a power level sufficient to be received by a receiver downstream of the second amplifier.

151. (NEW) An apparatus comprising:  
a first amplifier amplifying a plurality of optical signals, each having a different wavelength;  
a first dispersion compensator providing dispersion compensation to the amplified plurality of optical signals;  
a second amplifier amplifying the plurality of optical signals provided with dispersion compensation by the first dispersion compensator; and  
an enclosure housing the first and second amplifiers and the dispersion compensator.

152. (NEW) An apparatus as in claim 151, wherein the first and second amplifiers are erbium doped fiber amplifiers.

866150-6068050

153. (NEW) An apparatus as in claim 151, wherein the first dispersion compensator is a dispersion compensation fiber.

154. (NEW) An apparatus as in claim 151, wherein the first and second amplifiers have a combined gain so that the plurality of optical signals are output from the second amplifier at a power level sufficient to be received by a receiver downstream of the second amplifier.

155. (NEW) An apparatus as in claim 152, wherein the first and second amplifiers have a combined gain so that the plurality of optical signals are output from the second amplifier at a power level sufficient to be received by a receiver downstream of the second amplifier.

156. (NEW) An apparatus comprising:  
a dispersion compensator providing dispersion compensation to a plurality of optical signals, each having a different wavelength;  
a first amplifier positioned upstream of the dispersion compensator; and  
a second amplifier positioned downstream of the dispersion compensator, wherein a combined gain of the first and second amplifiers is sufficient to compensate a loss in the dispersion compensator and to produce the plurality of optical signals having



*at*  
*ant* . a second amplifier amplifying the multiplexed optical signal provided with dispersion compensation; and

a demultiplexer wavelength-division-demultiplexing the multiplexed optical signal, as amplified by the second amplifier, into respective optical signals.

161. (NEW) An optical transmission system as in claim 160, wherein a combined gain of the first and second amplifiers is sufficient to compensate a loss in the dispersion compensator and to produce the multiplexed optical signal having an output power for transmission downstream of the apparatus.

162. (NEW) An optical transmission system comprising:  
an optical transmitter providing an optical signal to an optical fiber;  
an apparatus, optically coupled to the optical fiber, including

a first amplifier amplifying the optical signal provided to the optical fiber by the optical transmitter,

a first dispersion compensator providing dispersion compensation to the amplified optical signal, and

a second amplifier amplifying the optical signal provided with dispersion compensation; and

an optical receiver receiving the optical signal amplified by

2025-09-08 09:00:00